



GLOBE VALVE (FORGED)

We, "Flow-Tech" are a leading manufacturer and Exporters of FORGED GLOBE VALVE. We have a widerange of FORGED GLOBE VALVE in A 105, F304, F316 and many more other metals on request. "FlowTech" FORGED GLOBE VALVE mainly Used in Process Industries and High Pressure Application inIndustries.

"Flow-Tech" FORGED GLOBE VALVE design is developed with following and using international Standard for having an International Competency with Global Manufacturers. We "Flow-Tech" follow an international standards and designs to get 100% superior quality

withworkmanship & service to maintain trust of our Clients and repeat order.



TECHNICAL DETAIL

DESIGN TYPE	OS & Y TYPE RISING STEM PRESSURE SEAL BONNET STRAIGHT TYPE Y-TYPE NEEDLE TYPE
MFG. STANDARD	API 602 / BS 5352
TESTING STANDARD	API 598 / ISO 5208/ BS 6755
SCREWED END	ASME B 1.20.1
SOCKET WELD END	ASME B 16.11
PRESSURE & TEMPERATURE RATING	ASME B 16.34
PRESSURE CLASS	800#, 1500#, 2500#,
VALVE SIZE	1/2" To 2" (15 mm TO 50 mm)
ENDCONNECTIONS	SCREWED (BSP / NPT)F / SOCKET WELD
MATERIAL OF CONSTRUCTION	ASTMA 105 / LF2 / F22 ASTMA 182 GR. F304 / F304L ASTMA 182 GR. F316 / F316L
OPERATIONS	HAND WHEEL /GEAR/ PNEUMATIC/ELECTRICALACTUATOR

FACE TO FACE DIMENSIONS

INCH	мм	800#	1500#	2500#	
1/2"	15	90.0	93.0	108.0	
3/4"	20	93.0	108.0	128.0	
1"	25	108.0	128.0	128.0	
11/4"	32	128.0	128.0	145.0	
11/2"	40	128.0.0	145.0		
2" 50		145.0			

TEST PRESSURE										
CLASS	BODY HYDRO TEST		SEAT HYDRO TEST		BACK SEAT TEST		AIR TEST			
	PSIG	KG/CM2	PSIG	KG/CM2	PSIG	KG/CM2	PSIG	KG/CM2		
800#	3000	211	2176	153	2176	153	100	7		
1500#	5546	390	4124	290	4124	290	100	7		
2500#	9314	655	6897	485	6897	485	100	7		

*Pressure Testing Time Will be 15 Sec. *Test With Water only.

**For More & Higher Size, Please Contact Us